



Value Each Gram A professional weighing products manufacturer and supplier

Specifications

- > ABS housing
- > Red LED display
- > RS232 interface
- > Counting function
- > Power saving mode
- > For 4*350Ω or 8*700Ω load cells
- > Programming zero tracking
- > Programming digital filter
- > Selectable Kg/lb units
- > Accumulation function
- > Optional adjusting pole neck
- > Optional Bluetooth output
- > Optional remote display
- > Optional s.s bracket

TechnicalData

Power 100-240V 50/60Hz - 12V adaptor or 110V/220V AC direct cable Rechargeable Battery: 6V4Ah Estimated Battery Life: 30 hours Charge Time: 8 Hours	Display Red LED (0.8")	Approval CE
Excitation Voltage DCSV 1-4 * 350Ω 1-8*700Ω load cells	Units Kg/lb	Packing Size 60*60*42cm (12pcs)
A/D Resolution 100,000	Output RS232	Packing Weight 22Kg (12pcs)
A/D Rate 40 times/second	Operating Temperature -10°C - 40°C	
Display Resolution 1/3,000 - 1/15,000	Storage Temperature -25°C - 55°C	
	Relative Humidity ≤80% non-condensing	

Models

Part No.	110058	110059
Models	X0AC	X0DC
U.P.(USD)	\$72.00	\$72.00
Power	110 or 220V	100-240V AC/DC Adaptor
Approval	CE	CE
Weight	1.7kg	1.7kg

Tel: +86-21-58273591 Fax: +86-21-58273591

Tel: +86-21-58250298

info@hiweigh.com

www.hiweigh.com