




## Specifications

- Adjusting pole neck <
- Smart-designed ABS housing <
- Free assembling of back case <
- Transient dust-cover included <
- High resolution till 1/30,000 <
- X704 with big red LED display <
- X706 with LCD display with backlit <
- Drive up to 4x350Ω or 8x700Ω load cells <
- Zero/Tare function <
- Counting function <
- Accumulating function <
- Response speed adjustable <
- Auto power saving <
- Multi-units exchange <
- Zero range programmable <
- G value (gravity) adjusting <
- Hold (animal weighing) (X706 only) <
- Checkweigh function (X706 only) <
- Optional RS232 interface - X7001 <
- Optional Bluetooth output - X7002 <
- Optional plastic wall bracket - X7003 <
- Optional s.s bracket - X7004 <

## TechnicalData

<b>Power</b> 100-240V 50/60Hz - 10V adaptor Rechargeable Battery: 6V3.2Ah Estimated Battery Life: 120 hours Charge Time: 8 Hours	<b>Display</b> X704 - LED (25mm) X706 - LCD (31mm)	<b>Protection</b> IP54
<b>Excitation Voltage</b> DC5V 1-4 * 350Ω load cells 1-8 * 700Ω load cells	<b>Units</b> Kg   lb   g   oz, etc.	<b>Approval</b> CE
<b>Analog Input Signal</b> 0.6mV/V - 3mV/V	<b>Output</b> RS232 (optional) Bluetooth (optional)	<b>Packing Size</b> 80 x 38 x 55cm
<b>A/D Rate</b> 20 times/second	<b>Operating Temperature</b> 0°C - 40°C	<b>Packing Weight</b> 16Kg (10pcs)
<b>Display Resolution</b> 1/3,000 - 1/30,000	<b>Storage Temperature</b> -25°C - 55°C	
	<b>Relative Humidity</b> ≤80% non-condensing	

## Models

Part No.	110047	110048	157013	157014	157015	157016
Models	X704	X706	X7001	X7002	X7003	X7004
U.P.(USD)	\$104.00	\$112.00	\$20.00	\$40.00	\$10.00	\$40.00
Display	LED	LCD	-	-	-	-
Protection	IP54	IP54	-	-	-	-
Weight	1.6kg	1.6kg	-	-	-	-