



## Specifications

- Rugged ABS housing <
- LCD display with backlight <
- High accuracy up to 1/60,000 <
- X7CC** - counting function <
- X7PC** - price computing function <
- Drive up to 4x350Ω or 8x700Ω load cells <
- Zero/Tare function <
- 18 PLU keys (9 direct) <
- Accumulating function <
- Auto power saving <
- Multi-units exchange <
- Response speed adjustable <
- Zero range programmable <
- Recall and clean function <
- Optional RS232 interface - X7001 <
- Optional Bluetooth output - X7002 <
- Optional stainless steel bracket - X7003 <
- Optional plastic wall bracket - X7004 <

## TechnicalData

<b>Power</b> 100-240V 50/60Hz - 12V adaptor Rechargeable Battery: 6V4Ah Battery Life: 130 hours (no backlight) Charge Time: 8 hours	<b>Display</b> LCD with backlight	<b>Protection</b> IP54
<b>Excitation Voltage</b> DC5V 1-4 * 350Ω load cells 1-8 * 700Ω load cells	<b>Units</b> Kg   lb	<b>Approval</b> CE
<b>Analog Input Signal</b> 0.6mV/V - 3mV/V	<b>Output</b> RS232 (optional) Bluetooth (optional)	<b>Packing Size</b> 76*46*34cm (8pcs)
<b>A/D Rate</b> 30 times/second	<b>Operating Temperature</b> 0°C - 40°C	<b>Packing Weight</b> 18Kg (8pcs)
<b>Display Resolution</b> 1/3,000 - 1/30,000	<b>Storage Temperature</b> -25°C - 55°C	
	<b>Relative Humidity</b> ≤80% non-condensing	



## Models

Part No.	110056	110057	157013	157014	157015	157016
Models	X7CC	X7PC	X7001	X7002	X7003	X7004
<b>U.P.(USD)</b>	<b>\$168.00</b>	<b>\$168.00</b>	<b>\$20.00</b>	<b>\$40.00</b>	<b>\$10.00</b>	<b>\$40.00</b>
Display	LCD	LCD	-	-	-	-
Protection	IP54	IP54	-	-	-	-
Weight	1.6kg	1.6kg	-	-	-	-