



Specifications

- Small s.s housing <
- IP54 protection <
- Stainless steel bracket <
- Red LED display <
- Ni-Mh rechargeable battery <
- 1-4*350Ω or 8*700Ω load cells <
- Programming zero tracking <
- Programming digital filter <
- Selectable Kg/lb units <
- RS232 interface <
- Hold function <
- Animal weighing <
- Counting function <
- Power saving mode <
- Accumulation function <
- Optional RS485 interface <
- Optional bluetooth output <
- Optional remote display <

Technical Data

Power 100-240V 50/60Hz - 12V adaptor Rechargeable Battery: 6V1,8Ah Estimated Battery Life: 30 hours Charge Time: 8 Hours	Display LED (0.56")	Protection IP54
Excitation Voltage DC5V 1-4 * 350Ω 1-8*700Ω load cells	Units Kg/lb	Approval CE
Analog Input Signal -1 - 10mV	Output RS232	Packing Size 38*26*28cm (6pcs)
A/D Resolution 100,000	Operating Temperature -10°C - 40°C	Packing Weight 7kg (6pcs)
A/D Rate 40 times/second	Storage Temperature -25°C - 55°C	
Display Resolution 1/3,000 - 1/30,000	Relative Humidity ≤80% non-condensing	



Models

Part No.	110051
Models	X8
U.P.(USD)	\$220.00
Housing	S.S
Protection	IP54
Weight	1kg