



Specifications

- 8" Touch Screen <
- High speed thermal Printer <
- Dynamic working mode - XM6D <
- Static working mode - XM6S <
- Wireless connection - XM6*FM <
- Standby working 40 hours with battery <
- Unlimited weighing records <
- Base on Windows CE 6.0* system <
- FREE Program upgrade <
- 2 Channels system as default <
- 4 / 6 / 8 channels system are optional <
- RS232, USB 2.0 as default <
- Wireless edition - USB 2.0 & WIFI as default <
- 30m working distance for wireless version <
- Display of weight of each wheel <
- Display of weight of each axle <
- Display of total truck weight <
- Excel, text or Database file output <
- Multi-languages support (default-English) <
- 4 Cores ARM CPU <
- Rugged ABS suitcase <
- 2GB memory with 4GB hard disk <
- SMS message and other application optional <



Models

Part No.	110063	110064	110065	110066
Models	XM6	XM6-4	XM6-6	XM6-8
U.P.(USD)	\$3,680.00	\$3,760.00	\$3,840.00	\$3,920.00
Wheels	2	4	6	8
Work Mode	Dynamic Static	Static	Static	Static
Weight	5.5kg	5.5kg	5.6kg	5.6kg

TechnicalData

Power 120V/240V AC/DC adaptor Rechargeable Battery: 6V10Ah Estimated Battery Life: 40 hours Charge Time: 8 Hours	Display 8" TFT	Temp. Coefficient 5ppm/°C
Excitation Voltage DC5V±2%	Units Kg lb	Protection IP54
Analog Input Signal -1 - 10mV	Output RS232 USB Bluetooth (optional) WiFi (optional)	Approval CE
Sampling Speed 200 times/second	Operating Temperature 0°C - 40°C	Packing Size 51*35*22cm
Non-Linearity < 0.01%	Storage Temperature -25°C - 55°C	Packing Weight 6.7kg
Power Consumption 70mA - standby 1000mA - printing	Relative Humidity ≤80% non-condensing	