

Clear Read  in the sun




Functions

- K7a with ABS housing <
- K7b with s.s housing - IP54 <
- K7i with s.s housing - IP65 <
- Stainless steel bracket <
- Big backlit FSTN LCD display <
- the weight can be read clearly even in the sun <
- With rechargeable 6V2.8Ah or 6V4Ah battery <
- 100-240v power source directly <
- kg/lb, g/oz units exchange <
- Real-time clock and date display <
- Checkweigh with three LED lights <
- Animal weighing function, accumulating, hold <
- x10 accuracy, counting, zero, tare, printing, etc <
- Default with 2 RS232 interface <
- Continuous, print or Modbus output <
- Option of Bluetooth output <
- Option of WiFi output <
- Option of Relay output <

TechnicalData

Power 100-240V AC direct cable Rechargeable Battery: 6V4Ah - K7a 6V2.8Ah - K7b K7i	Display FSTN LCD - 37mm	Approval CE
Excitation Voltage DC5V 1-4 * 350Ω load cells 1-8 * 700Ω load cells	Units Kg lb, g oz	Weight K7a - 2.4kg K7b - 2.6kg K7i - 2.8kg
Analog Input Signal ±10mV	Output RS232 * 2 Optional Bluetooth Optional WiFi	
A/D Resolution 1,000,000	Operating Temperature -10°C - 40°C	
A/D Rate 10 times/second	Storage Temperature -25°C - 55°C	
Display Resolution 1/3,000 - 1/30,000	Protection K7a - NA K7b - IP54 K7i - IP65	

Models

Part No.	110076	110077	110078
Models	K7a	K7b	K7i
U.P.(USD)	\$168.00	\$272.00	\$328.00
Power	100-240V	100-240V	100-240V
Approval	CE	CE	CE
Weight	2.6kg	2.8kg	2.8kg